

3G DS INTERPRETER

Installation Instructions



The user and the installer should be aware that changes and modifications to the equipment not expressly approved by Master Meter could void warranty and the user's authority to operate the equipment. Professionally trained personnel should install the equipment.

Sensus

Step 1

Clean meter top from any materials.



Step 2

Place Interpreter kit on meter; odometer facing 11 o'clock as shown.



Step 3

Twist Interpreter kit clockwise to where the register odometer is perpendicular to the flow line.



Step 4

To lock Interpreter kit in place, insert locking pin/arrow pointing up and push in until you hear a snapping sound.



Neptune

Step 1

Clean meter top from any materials.



Step 2

Place Interpreter kit on meter; odometer facing 11 o'clock as shown.



Step 3

Twist Interpreter kit clockwise to where the register odometer is perpendicular to the flow line.



Step 4

To lock Interpreter kit in place, insert locking pin/arrow pointing up and push in until you hear a snapping sound.



MM REV 9/27/2006



Master Meter, Inc. - 101 Regency Parkway, Mansfield, TX 76063
Toll Free: 800-765-6518 - Main Line: 817-842-8000 - FAX: 817-842-8100

www.mastermeter.com
info@mastermeter.com

3G DS INTERPRETER

Installation Instructions



The user and the installer should be aware that changes and modifications to the equipment not expressly approved by Master Meter could void warranty and the user's authority to operate the equipment. Professionally trained personnel should install the equipment.

Hersey

Step 1

Clean meter top from any materials.



Step 2

Place Interpreter kit on meter; odometer facing 11 o'clock as shown.



Step 3

Twist Interpreter kit clockwise to where the register odometer is perpendicular to the flow line.



Step 4

To lock Interpreter kit in place, insert locking pin/arrow pointing up and push in until you hear a snapping sound.



Badger

Step 1

Clean meter top from any materials.



Step 2

Place Interpreter kit on meter; odometer facing 11 o'clock as shown.



Step 3

Twist Interpreter kit clockwise to where the register odometer is perpendicular to the flow line.



Step 4

To lock Interpreter kit in place, using a tool with flat surface, insert locking pin all the way in until flush with plastic.



MM REV 9/27/2006



Master Meter, Inc. - 101 Regency Parkway, Mansfield, TX 76063
Toll Free: 800-765-6518 - Main Line: 817-842-8000 - FAX: 817-842-8100

www.mastermeter.com
info@mastermeter.com

